

TECHNICAL DATA SHEET (TDS)

ANTIGRAFFITI STRIP-VAPOR

ID Product Code 031



Pag | 1

Anti-graffiti protective product.

Product description:

Anti-graffiti liquid product, microcrystalline waxes based, for protection of external facades, statues, decorations and walls against writing and drawing executed with tempera, paint, liquid and most of spray paints on the market. STRIP-VAPOR, thanks to its special water-based formulation, seals porosity of the material (letting the stone breath) and does not allow the paint to penetrate into porosity of stone. It forms an imperceptible and invisible layer of product. This layer of product, once the graffiti cleaning has to be done, will be removed using a high pressure cleaner with hot water or steam jets, or by mechanical action: removing the layer of protective wax, they also will wear away the paint stains.

Chemical characteristics:

Appearance	Liquid
Color	White
Odor	Odorless
Specific gravity at 20° C (68° F)	1,00 ± 0,02
Hydro-solubility	Soluble in every ratio
pH	8,50 ± 0,02
Shelf life at 20°C (68° F)	24 months in original container

Instruction for use

Surface preparation: surface must be dry and clean; possibly stains, mildew, crusting must be taken away, otherwise they will be encapsulated and protected by the resin films and their subsequent removal would be difficult.

Application: by cloth, brush, roller or spray. Apply STRIP VAPOR on the surface to be treated, taking care to apply it evenly. For a good impregnation it is recommended to apply 2 coats. Once applied, STRIP VAPOR gives a light satin effect to the surface; in case a more shiny effect is desired, it is necessary to gently rub the surface with a cloth. The anti-graffiti will start its function after about 12 hours (curing time).

Removal: in the case treated surfaces are stained by graffiti and written with spray or liquid paints, it is possible to remove the writings with steam or hot water jets in order to melt the protective and consequently remove the paint. Alternatively, it is possible to apply mechanical action using abrasive pads such as Scotch Brite® or brushes.

If the paint is not entirely removed, we suggest to use our Paint Stripper WALL CLEAN.

After removal, it is necessary to repeat the application of STRIP VAPOR to continue the protection.

Suggestion for use and recommendations:

- On very absorbent materials, we suggest to apply first layer of product, wait 30 minutes and then proceed with second layer.
- Surfaces to be treated, before application, have to be dry.
- In case of treatment of statues, vases, decorations, make attention to protect interstices.
- Read carefully recommendations printed on label and perform a preliminary test on a small area before actual use.

Application surfaces

Marble, granite, marble-cement, marble resin, calcareous stones, terracotta, bricks and concrete.



DISCLAIMER All data indicated in this leaflet are the results of tests and experiments carried out in our laboratories and through reliable operators in the stone business and have to be considered reliable. Because of the many factors which can influence them, the information here reported do not constitute implicit or formal guarantees. The end user undertakes the responsibility in the usage of the product making sure to experiment the product characteristic as preventive measure. Bellinzoni srl reserves the right to make changes to the products shown in this card, at any time without prior notice. The pictures shown are approximate, as a printed reproduction causes inevitable differences.



TDS N°
031

TECHNICAL DATA SHEET (TDS)

Application tools



Brush



Roll



Cloth


 Wax spreader
 fleece


Sprayer

Pag | 2

Coverage

For protection of marble and granite polished or grinded after grid 800, with 1 liter (1 quart) of product is possible to treat 10/15 sqm (110/160 sq.ft.) In case of calcareous stone, limestone, sand stone, concrete polished or grinded after grid 800 with 1 litre of product, it is possible to treat 5/10 sqm (50/110 sq.ft.).

Safety procedures

As far as the proper working procedures is concerned, we recommend to consult Material Safety Data Sheets issued according to E.U. rules and to follow your national laws concerning safety in the working place. MSDS is available on our web site www.bellinzoni.com.

Packing

Item N°	Content	Pcs
031CBEL01	1,00 lt (1,05 qt)	12
031CBEL05	5,00 lt (1,32 gal)	4
031CBEL025	25,00 lt 6,60 gal)	1

The composition of tins and drums is High Density Polyethylene (HDPE). After use, comply with the local and national regulations currently in force regarding recycling. Our packing is conformed as per U.N. rules for inland transport (A.D.R.) and by sea (I.M.O.) for transportation via air refer to updated rules (I.A.T.A.). For further information regarding transport please check MSDS.

Trademark and Origin of the good

BELLINZONI® is a registered trademark of Bellinzoni company. The law considers a trademark to be a form of property and any misuse can be persecuted by law. Bellinzoni s.r.l. declares that our product ANTIGRAFFITI STRIP-VAPOR is MADE IN ITALY.



DISCLAIMER All data indicated in this leaflet are the results of tests and experiments carried out in our laboratories and through reliable operators in the stone business and have to be considered reliable. Because of the many factors which can influence them, the information here reported do not constitute implicit or formal guarantees. The end user undertakes the responsibility in the usage of the product making sure to experiment the product characteristic as preventive measure. Bellinzoni srl reserves the right to make changes to the products shown in this card, at any time without prior notice. The pictures shown are approximate, as a printed reproduction causes inevitable differences.



TDS N°
031